



The Wood Finish People

CLEAR WOOD FINISH ® BRUSHING LACQUER

DESCRIPTION: CLEAR WOOD FINISH is an Interior brushing nitrocellulose lacquer. It dries by solvent evaporation and can easily be repaired, buffed and recoated, any time in the future, without lifting, wrinkling or totally removing the old finish. CLEAR WOOD FINISH is ideal for all interior wood surfaces, except wood floors. CLEAR WOOD FINISH acts as its own sealer or use LACQUER SANDING SEALER. Excellent for arts and crafts, decoupage and also has adhesion to metals. Non-toxic when dry.

SPECIFICATIONS

<p>SOLVENT TYPE Lacquer Thinner</p> <p>RESIN TYPE Nitro-cellulose</p> <p>FINISH Gloss 90+ %, Semi-Gloss 28-32 %, Satin 12-18 %</p> <p>COLORS Clear</p> <p>BASES Not available</p> <p>VISCOSITY AT 77° F (25° C) 18-20 sec. EZ #3 (Zahn cup)</p> <p>VOC CONTENT 680 g/L (as supplied). Meets the Federal AIM Rule.</p> <p>SOLIDS BY VOLUME. SOLIDS BY WEIGHT. 18 ± 1 % 26 ± 1 %</p> <p>WEIGHT PER GALLON 7.4 – 7.6</p> <p>COMPOSITION BY WEIGHT Vehicle 26 % Nitro-cellulose 10.5 % Plasticising alkyd 15.5 %</p> <p>RECOMMENDED FILM THICKNESS PER COAT Wet: 3 mils Dry: 0.5 mils Apply three coats for best performance. Six coats in moisture prone areas.</p> <p>PRACTICAL COVERAGE PER COAT AT THE RECOMMENDED DRY FILM THICKNESS 400 - 500 sq.ft. /gal. depending on surface conditions</p> <p>AVERAGE DRY TIME AT 77° F (25° C) To touch: 30 minutes Recoat: 2 hours Tack-free: 60 minutes To handle: 18 hours</p> <p>APPLICATION EQUIPMENT Brush, Pad, Roller or Aerosol.</p> <p>PACKAGING ½ Pints, Pints, Quarts, Gallons, 5 Gallons, Drums, Aerosols.</p> <p>MATERIAL SAFETY DATA SHEET Available on request</p>	<p>SURFACE PREPARATION All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, and other contaminants. Remove all loose, peeling or cracked coatings. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded, and cleaned.</p> <p>THINNING RECOMMENDATIONS CLEAR WOOD FINISH is supplied at application viscosity.</p> <p>CLEANUP Use Lacquer Thinner for cleanup. Dispose of waste in accordance with applicable laws and regulations.</p> <p>PRIMER CLEAR WOOD FINISH can be applied over Deft's LACQUER SANDING SEALER, which will speed up production, by better filling and easy sanding. CLEAR WOOD FINISH can be used without a sealer, directly on wood.</p> <p>OTHER SYSTEM INFORMATION CLEAR WOOD FINISH can be used over most stains. Try a small test area before doing the entire project. CLEAR WOOD FINISH can be used over most metals. CLEAR WOOD FINISH is not recommended for areas of heavy use or where prolonged water exposure can be expected. For those areas, DEFTHANE polyurethane varnish is recommended.</p> <p>IMPORTANT NOTE In moisture areas (kitchens, bathrooms, window sills etc.) white water spotting will occur when the filmthickness is less than 4 or 5 mils. Apply at least six full coats of CLEAR WOOD FINISH to prevent white water spotting.</p> <p>WARNING DO NOT APPLY CLEAR WOOD FINISH over varnishes, enamels (or any other product that dries by oxidation), it may result in lifting or wrinkling.</p> <div style="border: 2px solid red; padding: 5px;"> <p>FLAMMABLE The solvents in CLEAR WOOD FINISH are flammable provide ventilation and avoid all ignition sources during application and drying.</p> </div>
---	---